

## 15" LCD MONITOR



Monitor LCD professionale con matrice attiva TFT ad alta risoluzione in grado di ottenere una risoluzione di 1024 X 768

Il tipo di connessione video di tipo BNC con rinvio e l'elevata qualità ne fanno un monitor perfetto per la videosorveglianza.

Oltre al segnale video composito PAL è possibile un ulteriore input di tipo digitale DVI o SVGA attraverso un adattatore in dotazione.

Il monitor dispone di un supporto da tavolo ed è predisposto per il fissaggio a muro con supporti VESA

### Caratteristiche

- Dimensione: 15".
- Tempo di risposta: 12 ms.
- Luminosità: 250 cd/m<sup>2</sup>.
- Contrasto: 500:1.
- Risoluzione: 1024 x 768 pixels.
- PAL video composito looping input.
- VESA compatibile.
- 2 casse audio integrate

Category	Description
Type of panel	LCD-TFT active
Size	15 inch diagonal, 38 cm
Pixel pitch	0.297 (l) x 0.297 (h) mm
Luminosity	250 cd/m <sup>2</sup> typical
Contrast	500 : 1
Response time	12 ms typical
Angle of view	130° (h) x 120° (v)
Resolution	1024 (l) x 768 (h)
Number of colours	16.7 M
Video input	Video composite on BNC, looping input Digital input on DVI connector Analogical input per D-Sub/DVI adapter
Display area	304 (l) x 228 (h) mm
Power supply	External 100 - 240 V / 60-50 Hz - 12 Vdc 4.2 A
Consumption	25 watts (maximum) - 3 watts (Standby)
Audio	2,5 watts on 2 loudspeakers 2 RCA connectors
Frequency	Horizontal: 30 - 82 kHz - Vertical: 50-75 Hz
Dimensions	375 (l) x 380 (h) x 140 (p) mm
Unit weight	Without packaging: 3.0 kg With packaging: 3.6 kg
Range of temperature	+5° to +35° - Humidity: 20% to 80%
Temperature of storage	-20° C - 60° C - Humidity: 20% to 80%
Standards	UL, CUL, FCC-B, CB, CE, TUV/GS
Medium	Vesa compatible
Language	French, English, German, Spanish, Italian



NMLCD1503X  
Front view



NMLCD1503X  
Side view



NMLCD1503X  
Connectic