

19" LCD MONITOR



Monitor LCD professionale con matrice attiva TFT ad alta risoluzione in grado di ottenere una risoluzione di 1280 x 1024

Il tipo di connessione video di tipo BNC con rinvio e l'elevata qualità ne fanno un monitor perfetto per la videosorveglianza.

Oltre al segnale video composito PAL è possibile un ulteriore input di tipo digitale DVI o SVGA attraverso un adattatore in dotazione.

Il monitor dispone di un supporto da tavolo ed è predisposto per il fissaggio a parete con supporti VESA.

Caratteristiche

- Dimensione: 19".
- Tempo di risposta: 8 ms.
- Luminosità: 400 cd/m².
- Contrasto: 550:1.
- Risoluzione: 1280 x 1024 pixels.
- PAL video composito looping input.
- VESA compatibile.
- 2 casse audio integrate

Category	Description
Type of panel	LCD-TFT active
Size	19 inch diagonal, 48 cm
Pixel pitch	0.294 (l) x 0.294 (h) mm
Luminosity	400 cd/m ² typical
Contrast	550 : 1
Response time	8 ms typical
Angle of view	140° (h) x 135° (v)
Resolution	1280 (l) x 1024 (h)
Number of colours	16.6 M
Video input	Video composite on BNC, looping input Digital input on DVI connector Analogical input per D-Sub/DVI adapter
Display area	376 (l) x 301 (h) mm
Power supply	External 100 - 240 V / 60-50 Hz - 12 Vdc 4.2 A
Consumption	50 watts (maximum) - 3 watts (Standby)
Audio	2.5 watts on 2 loudspeakers 2 RCA connectors
Frequency	Horizontal: 30 - 82 kHz - Vertical: 50-75 Hz
Dimensions	425 (l) x 425 (h) x 175 (p) mm
Unit weight	Without packaging: 6 kg With packaging: 7.5 kg
Range of temperature	+5° to +35° - Humidity: 20% to 80%
Temperature of storage	-20° C - 60° C - Humidity: 20% to 80%
Standards	UL, CUL, FCC-B, CB, CE, TUV/GS
Medium	Vesa compatible
Language	French, English, German, Spanish, Italian



NMLCD1904X
Front view



NMLCD1904X
Side view



NMLCD1904X
Connectic