

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20A enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

***At a Glance***

- Single speed-dial button with blue backlight;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation & Noise suppression;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

- Front panel: Aluminum alloy
- Camera: 2M pixels, automatic lighting
- Button: 1 call button
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: 1ch input/output(selectable)
- RS485 port: Support
- RF reader: 13.56MHz&125kHz, NFC (only Android)
- Relays out: 2
- Inputs: 2
- Microphone: 1
- Speaker: 1
- Tamper alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- IP Rating: IP65
- Dimension (HxWxD): 145x85x22mm
- Installation: Flush-mounted or Wall-mounted
- Working Humidity: 10~90%
- Working Temperature: -30°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C

Akuvox
Open A Smart World

10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akuvox.com

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833),

SIP Info

- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd party video components, e.g. NVRs

Networking and Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX

Capacity

- User: 5,000
- Card: 25,000

Card Type

- EM card
- Mifare card
- DesFire card (EV1/EV2/EV3)

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)