

Perfect Doorphone choice for daily life

Sometimes running or replacing cables is not cost effective or near impossible especially in older apartment buildings or established homes or businesses.

A cost-effective alternative is to use the mobile networks to bypass cables altogether. Akuvox's Video Doorphone R29C-L is designed to remove cables from the solution solving what has become an expensive problem for many.

At a Glance

- Aluminum panel with 7inch touchscreen;
- Android operation system;
- Wide-angle camera: 105°(H) / 55°(V);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Multi-way access feature including: Face, EM/Mifare Card, PIN, BLE & QR code;
- Using LTE technology to combine minimum installation when installed at sites;
- Flush-mounted & surface-mounted;



Physical & Power

- | | |
|---|---|
| <ul style="list-style-type: none"> • Front panel: Aluminum • Display: 7 Inch IPS LCD, 800×1280 • Screen: 7 Inch capacitive touch screen • Main Camera: 2M pixels, automatic lighting • Auxiliary Camera: 1M pixels • Infrared (IR) LED: Support • Light sensor: Support • White Light LED: Support • Motion sensor: Support • Wiegand port: 1ch input/output(selectable) • RS485 port: Support • RF reader: 13.56MHz&125kHz, NFC (only Android) • Relays: 2 • Inputs: 2 | <ul style="list-style-type: none"> • Microphone: 1 • Speaker: 1 • BLE: Support BT5.0 • Ethernet port: RJ45, 10/100Mbps adaptive • SIM Card Slot: Support • 12V DC connector • IP Rating: IP65 • Installation: Flush-mounted & Wall-mounted • Dimension (HxWxD): 324x130x33mm • Working Humidity: 10~90% • Working Temperature: -20°C ~ +55°C • Storage Temperature: -40°C ~ +70°C |
|---|---|

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ, G.729
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 25fps
- Viewing angle: 115°(H) / 63°(V)
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Multi-way Unlock: Face, EM/MIFARE Card, PIN, QR, and BLE
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX
- Face Recognition Speed: <500ms
- Face Recognition Accuracy: 99%

Capacity

- User: 20,000
- Contact: 3,000
- Face Template: 20,000
- Card: 100,000
- PIN: 20,000

Card Type

- EM card
- MIFARE card
- DESFire card (EV1/EV2/EV3)
- Felica card

Networking and Protocol

- LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13 / B18/B19/B20/B25/ B26/B28
- LTE-TDD: B38/B39/B40/B41
- WCDMA: B1/B2/B4/B5/B6/B8/B19
- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP,

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)