

Premium touch screen for your home

The Akuvox S562W-2 multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.



At a Glance

- Ultra-clear, stylish appearance;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Completely solve the stability problem of Wi-Fi with Wi-Fi 6;
- Two-way audio communication with other units in the 2-Wire IP network;
- Powered by NS-2 or external source;
- Super long transmission distance via 2-wire cable
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

Physical & Power

- | | |
|--|--|
| • Front panel: Plastic | • Microphone: -42dB |
| • RAM / ROM: 128MB / 128MB | • Speaker: 4Ω / 2W |
| • Display: 7 Inch IPS LCD | • 2-Wire Port: 2 |
| • Screen: 7 Inch Capacitive Touch Screen | • Ethernet Port: 1xRJ45, 10/100Mbps |
| • Wi-Fi: IEEE802.11 b/g/n/ax, @2.4GHz | • 48V DC Connector (if not using NS-2) |
| • RS485 Port: 1 | • Tamper Resistant: Support |
| • Relay Out: 1 | • Installation: Wall-mounted & Desktop |
| • Bell in: 1 | • Dimension: 216.4x118.8x21.7mm |
| • Alarm Input: 8 | • Working Humidity: 10~90% |
| | • Working Temperature: -10°C ~ +45°C |
| | • Storage Temperature: -20°C ~ +70°C |