

UT363S is a stable, safe and reliable split-type anemometer, featuring quick detection, low consumption and high accuracy. It can be widely used in mining, electrical, iron and steel, petrochemical, energy-saving, navigation, fan manufacturing, exhaust ventilation, sporting and more sectors.



UT363S

| Specifications | Range | Accuracy |
|---------------------|--------------------------------------|-----------------|
| Certificates | CE, UKCA | |
| Wind speed | 0.4~30m/s | ±(5%+0.5m/s) |
| | 1.4~108km/h | ±(5%+1.5km/h) |
| | 78~5905ft/min | ±(5%+100ft/min) |
| | 0.7~58knots | ±(5%+1knots) |
| | 0.8~67mph | ±(5%+1mph) |
| Temperature | -10~50°C/14~122°F | ±2°C/±4°F |
| Wind scale | 0~12 | ±1 |
| Sampling rate | 0.5s | |
| Units | m/s, km/h, ft/min, knots, mph, °C/°F | |
| Working temperature | 0°C~40°C | |

| Features | |
|------------------------|---------------------------|
| Overload indication | Auto range/auto power off |
| Low battery indication | Data hold |
| MAX/MIN/AVG | Backlight |

| Characteristics | |
|------------------------------|---------------------------|
| Standard accessories | Batteries, English manual |
| Power | 1.5V battery (R03) x 3 |
| Display | 35 x 32mm |
| Product size | 120 x 53 x 43mm |
| Product net weight | 365g |
| Standard individual packing | Gift box, blister |
| Standard quantity per carton | 20pcs |
| Standard carton measurement | 550 x 295 x 350mm |
| Standard carton gross weight | 7.2kg |