

75" Smart Interactive Display

MW3575-U-E



Features

- 4K UHD anti-glare display delivers images with extreme detail.
- Zero bonding technology between lcd panel and cover glass brings brighter viewing and smoother touching experience.
- Ultra-narrow and equal-width bezel design for perfect aesthetics.
- Minimalist geometric line design and smooth border outline, elegant and attractive.
- Dual Wi-Fi modules with both Wi-Fi and hotspot support.
- Dual-channel, 6-array speaker brings high-quality surround sound.
- High-precision infrared touch technology allows up to 20-point touch, realizing smooth co-authoring.
- Bluetooth 5.2 offers higher data transmission rate, and lower power consumption.
- 4K UI, mobile-level operation, just like use a mobile phone.
- A variety of quick tools, such as annotation, screenshot, etc., improve usability and interaction efficiency.
- Wireless screen mirroring from various operating systems such as Android, iOS and Windows to the display with one touch


- Fast file transfer. Allows users to quickly transfer files to the display via a QR code.
- OTA remote upgrade. The system can be upgraded online without backing up data.


Specifications

| Panel | Description |
|---------------------------------|---|
| Backlight | DLED backlight |
| Panel size | 75 inches |
| Resolution | 3840*2160 |
| Brightness (cd/m ²) | 350 |
| Contrast Ratio | 1200:1 |
| Response Time (ms) | 8 |
| Color Support | 1.07B |
| Viewing Angle (H/V) | 178° /178° |
| System | Description |
| CPU | RK3588: 4-core A76 (2.4G) + 4-core A55 (1.8G) |
| CPU Frequency | 2.4GHz |
| RAM/ROM | DDR4: 8GB eMMC: 64GB |
| System Compatibility | Android 12.0 |
| Touch | Description |
| Touch Control | Infrared touch screen, 20-point multi-touch at most |
| Touch Precision (mm) | ± 1 |
| Recognizable Object | 5 points 2mm |
| Glass | 4mm tempered glass, level 7 on Mohs hardness scale, anti-glare |
| Touch Response Time (ms) | ≤ 10 |
| Touchscreen Input | Opaque objects (e.g. finger, pen, etc.) |
| Interface | Description |
| Video Input | 3*HDMI IN (4K@60) |
| Video Output | 1*HDMI OUT (4K@60) |
| Audio Input | 1*AUDIO IN |
| Audio Output | 1*AUDIO OUT |
| Other Interfaces | 1*RS232、 3* USB 3.0、 1* USB Type C、 1* USB Type B |
| Network | 2*RJ 45,10M/100M/1000M adaptive Ethernet Interfaces |
| Audio | Description |
| Frequency domain | 80Hz~20kHz |
| Speaker | Left channel 17W: 1*treble (8 Ω 5W) + 2*bass (4 Ω 6W) Right channel 17W: 1*treble (8 Ω 5W) + 2*bass (4 Ω 6W) |
| Wi-Fi | Description |
| WiFi Configuration | Wi-Fi6 + Wi-Fi5 dual-module, supports 5G/2.4G |
| WiFi Performance | 30 m ² coverage, 20m transmission distance in open space |

| Bluetooth | Description |
|---------------------------------|--|
| Bluetooth Version | 5.2 |
| Bluetooth Performance | 10m transmission distance in open space |
| OSD | Description |
| Multi-Language | 24 (Simplified Chinese, Traditional Chinese, English, Japanese, Arabic, French, Spanish, Portuguese, German, Italian, Dutch, Polish, Korean, Catalan, Galician, Vietnamese, Bulgarian, Kazakh, Russian, Ukrainian, Thai, Uzbek, Hungarian, Croatian) |
| VESA | Description |
| Wall mount hole (mm) | 600*400 |
| Wall mount screw | 4-M8 screw hole |
| General | Description |
| Power Supply | AC 100 to 240V, 50/60Hz |
| Overall Power Consumption (W) | ≤320 (on without OPS) |
| Standby Power Consumption (W) | <0.5 |
| Product Dimensions (W*H*D) (mm) | 1720*1035*89 |
| Package Dimensions (W*H*D) (mm) | 2115*1336*222 |
| Weight (Kg) | Net weight: 50.0 Gross weight:58.8 |
| Operating Temperature | 0 to 50° C |
| Operating Humidity | 10% to 90% (non-condensing) |
| Storage temperature | -20 to 60° C |
| Storage humidity | 0% to 95% (non-condensing) |
| Accessories Included | 1*power cord、2*touch pen、1*quick guide |


Dimensions





Interface

Front interfaces:



Side interfaces:



Ordering Information for Optional Accessories

| Model | Remarks |
|--------------|--|
| HB-7199-CA08 | Pluggable 4K Camera Microphone Module |
| HB-7199-MC04 | Pluggable MIC Module |
| HB-7199-TP | Wireless screen sharing dongle |
| HB-4365 | 65" to 86" Wall mount |
| HB-8765-S | 65" to 86" Mobile stand |
| HB-7099-M1 | Pluggable PC module with i5 processor (Windows 10, not activated) |
| HB-7099-S1 | Pluggable PC module with i7 processor (Windows 10, not activated) |
| LIS-WIN10-V | OS-Windows 10-1 to 1 license-IoT Enterprise Value version (with i5 processor OPS PC module) |
| LIS-WIN10-H | OS-Windows 10-1 to 1 license-IoT Enterprise High End version (with i7 processor OPS PC module) |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.