

# MT-CVIA72B12

Mtechnology HDCVI motorised camera

300°/s

1080P (25FPS)

1/2.8" Sony© Exmor

Minimum illumination 0.05 Lux

Varifocal lens 5.1~61.2 mm

Exterior rated to IP66 / IK10



HDCVI Speed dome camera

High speed 300°/segundo

12X Optical zoom

16X Digital zoom

1/2.8" Exmor CMOS

HD 1080p (1944x1092)

HDCVI output

Varifocal lens 5.1~61.2 mm

0.05 Lux/F1.6 (Colour), 0.005 Lux/F1.6 (B&W)

IR Cut

Audio

Alarms

Pelco P/D protocols supported

OSD Menu

Weatherproof IP66

Ceiling installation

# MT-CVIA72B12

Brand	Mtechnology
Range	HDCVI 1080p PRO
Image sensor	1/2.8" 2 Megapixel Exmor CMOS
Resolution	1080p (25fps) / 720p (50fps)
Video output	1 x BNC HDCVI format
Minimum illumination	0.05 Lux (colour) / 0.005 Lux (B/N)
Lens	Varifocal 5.1~61.2 mm (Optical Zoom 12X)
Digital zoom	16X
Basic functions	OSD menu, Day/Night with IR-CUT (ICR)
Configurable OSD functions	DWDR, BLC, HLC, 2D-3DNR, AWB, AGC, Privacy Masking
Pan/Tilt Range	Horizontal: 0°~360°, Vertical: -2°~90° auto flip 180°
Manual speed	Horizontal: 0.1° ~300°/s, Vertical: 0.1° ~120°/s
Speed between Presets	Horizontal: 300° /s, Vertical: 200° /s
Preset positions	255, position(s), 5 pattern(s), 8 tour(s), 5 Auto Scan(s)
Communication	RS485, Protocols Pelco P / Pelco D
Audio	1 input (Line In)
Alarms	2 inputs / 1 relay NO/NC
Power supply	AC 24 V / 1.5 A
Degree of protection	Weatherproof IP66, Vandal-proof IK10
Temp. operation	-40° C ~ +60° C
Dimensions (without support)	155 mm (He) x 170 (Ø) mm
Weight (without support)	1900 g