



1CH Passive HD Video Balun

Passive, no power required, Plug-and-play; Real-time and stable HDCVI/HDTV/AHD/Analog

FEATURES

- Real-time transmission over UTP CAT5E/6 cable
- Passive, no need for power supply.
- With female BNC connector, and pluggable screw terminal connections.

TECHNICAL SPECIFICATIONS

Item	MT-UTP101PHD2
Video Port	1 channel
Transmission Distance (with passive product)	HDCVI-720P:500m; HDCVI-4MP:150m; HDTV-720P/1080P: 240m; AHD-720P/960P: 500m; AHD-1080P:420m Analog Video:600m;
Coaxial Video Port	Male BNC Port
Twisted-pair Video Port	2-channel screw push terminal
Video Compatibility	HDCVI/HDTV/AHD, PAL/NTSC/SECAM Video
Bandwidth	0 ~ 75MHz
Anti-interference	>60dB
Coaxial Port Protection	2KV Per: IEC61000-4-5 2KV(different mode) 4KV(common mode)
Twisted-pair Port Protection	Per: IEC61000-4-5 Level 3,1a Contact Discharge,
ESD	Level 3,1b Air Discharge
Working Temperature	-10 ~ 55°C
Storage Temperature	-20°C ~ 70°C
Humidity (Non-condensing)	0 ~ 95%
Out Shell	ABS
Weight	18g