

SF-SD8630IT-FTVI

Motorized HDCVI camera 240°/s
Intelligent detection: Auto-tracking
1080p(25FPS) / 1/3" Progressive
CMOS
IR LED range 120m
Optical Zoom 30X (4~120 mm)
Suitable for exterior IP66



Safire
HDTV I Auto-tracking motorised dome camera
Average speed 240°/segundo
30X Optical zoom - 16X Digital zoom
1/3" Progressive Scan CMOS
HD 1080P (1920x1080)
HDTV I and CVBS outputs
4.0~120.0 mm Varifocal lens
0 Lux - IR Range 120 m
IR Cut
Pelco P/D protocols supported
OSD Menu
Intelligent detection: Auto-tracking
Weatherproof IP66
Bracket not included (see compatible brackets)

Specifications

Brand	SAFIRE
Image sensor	1/3" Progressive Scan CMOS
Resolution	1080p (1920x1080) at 25 FPS
Video output	BNC HDTV format and BNC CVBS format
Minimum illumination	0.05 Lux (colour) / 0.01 Lux (B/N)
Infrared lighting	Automatic IR LED's, range 120 metres
Lens	Varifocal 4.0 – 120.0 mm (Optical Zoom 30X)
Digital zoom	16 X
Electronic shutter	1/1s–1/10,000s
Day / Night	Removable mechanical ICR filter
Noise reduction	3D-NR
Gain Control	Auto / Manual
Backlight compensation	BLC / WDR
White balance	Auto, ATW, Interior, Exterior, Manual
Privacy masks	Up to 8 areas
Auto Tracking	Motion tracking (Person)
Pan/Tilt Range	Horizontal: 0°–360°, Vertical: -15°–90° auto flip 180°
Manual speed	Horizontal: 0.1°–160° /s, Vertical: 0.1°–120° /s
Speed between Presets	Horizontal: 240° /s, Vertical: 200° /s
Preset positions	300 preset, 4 auto pattern, 8 auto tour, auto pan, auto scan
Communication	RS485, Pelco P / Pelco D / SAFIRE
Audio	No
Alarms	2 IN / 1 OUT
Power supply	AC 24 V / 2A, 30 W
Temp. operation	-30° C ~ 65° C
Degree of protection	IP66 / Surges 4000V
Dimensions (without support)	353.4 mm (H) x 220 (Ø) mm
Weight (without support)	4500 g