

# GM1992V<sub>2</sub>

Monitor CCTV LCD-LED 19"



## DESCRIZIONE

Monitor CCTV LCD-LED 19" - Ingressi video BNC-VGA - Formato 4:3 - Colore e B/N - Attacco VESA - Completo di supporto da tavolo. Funzione Power-UP che permette la riaccensione automatica del monitor dopo un Black out.

## Caratteristiche modello MNT19BNCB

Display	Visible Diagonal	19"
	Display Color	16.7 M
	Brightness	300cd/m <sup>2</sup>
	Aspect ratio	4:3
	Contrast Ratio	1000:1
	Viewing Angle	170° / 150° (H/V)
	Pixel Pitch	0.294mm (H x V)
	Resolution	1280 x 1024 @ 60Hz
	Response Time	5ms
Signal	Input	15pin D-Sub, HDMI, Video Input (BNC), Video Output (BNC loop through)
Scanning Frequency	Horizontal	30 ~ 80KHz
	Vertical	56 ~ 75Hz
Max. Resolution		1280 x 1024 @ 75Hz
Plug & Play		DDC 1/2B
Function		Sleep, Timer, Video Mode (video/S-video select), Priority source select

Other Features	Vesa Arm	7,5 x 7,5 cm
	Kensington Lock	NO
	Audio System	8 ohms / 2 W
	Stand	Double HINGE
User Controls		Brightness, Contrast, Color, Hue, Sharpness, Color temperature, Picture mode Select, Image Aspect ratio,
OSD		11 languages
Power	Input voltage	12 VDC 2A -
	Consumption	1,2A
	Type	external 100-240V AC, 50/60Hz,
Operating Condition	Temperature	0° C - 40°C
	Humidity	Less 90%
Storage Condition	Temperature	-25° C - 60°C
	Humidity	20% - 90%
Emissions Standard		CE
Dimension	With stand	425 x 425x 180 mm
	Without stand	425 x 425x 65 mm
Weight	Unit	4.8Kg

Tutti i marchi citati appartengono ai legittimi proprietari.

L'aspetto esteriore e le caratteristiche tecniche possono essere modificati in qualunque momento.