



Product series	Industrial
Sensor	2 MP 1/2.8" CMOS
Resolution	1920(H)x1080(V)
Minimum Illumination	0.05Lux(Color Illumination), F1.2
Electronic Shutter	1/30 Second -1/10000 Second
Wide Dynamic Range	≥80db
Black-light Compensation	Support
S/N	≥48db
IR	12-20m
Lens	2.8mm, 4mm, 8MM M12 Fixed aperture F1.8
FOV	2.8mm=H*V 96*55°/4mm= H*V 73*41°/8mm= H*V 36*20
Video Compression Standard	H.264
Compression Output Rate	512Kbps-8Mbps
Image Resolution	Main Stream:1080P(720P) @ 30fps, Sub Stream1:VGA/WD1/D1/QVGA/CIF @15FPS Net transmission stream: dynamic (adjustable)
CBR/VBR	Support
Network port	10M/100M adaptive Ethernet port
Network Protocol	TCP/IP, HTTP, DHCP, RTSP, NTP, FTP
N9M	Support
ONVIF	Support
Client Preview	Built-in WEB server; Support IE browser
Installation features	Installs on the wall of the vehicle
Temperature	-40°C +70°C
Humidity	0% - 90%
Power Supply	DC 12V/POE
Waterproof Class	IP6K9K/IP67
Power Consumption	<2w(day) <5w(night)
Dimension (mm)	109mm(L)*95.3mm(W)*55.4mm(H)