

MT-IPDE14AI

4MP Smart Dual Light Eco IP Dome Camera

Easy to install. Built to perform.



Smart Dual Light IR 30 m + warm light 30 m, intelligent switching for 24/7 color imaging	Ultra-Low Light 0.01 Lux @ F2.0 for outstanding low-light performance	Vandal-Proof IK10 impact resistance with IP67 weather protection in metal housing	Easy Integration PoE, built-in mic, ONVIF, MicroSD up to 256 GB
--	---	---	---

Compact Dual Light Dome with Professional Performance

Smart dual light technology combines infrared and warm light illumination for optimal imaging in any condition. The compact vandal-proof dome design with IK10 protection and IP67 weatherproofing ensures reliable operation in demanding outdoor environments. Built-in microphone and PoE connectivity simplify installation.

FEATURES

- 4MP 1/2.8" CMOS sensor, 0.01 Lux @ F2.0 low-light performance
- H.265/H.264 video compression, up to 4MP @ 20/25 fps
- Smart Dual Light: IR 30 m + warm light 30 m with intelligent switching
- Fixed 2.8 mm lens with F2.0 aperture
- Digital WDR, 3D NR, BLC, Mirror for superior image quality
- Built-in microphone for audio recording
- MicroSD card slot up to 256 GB for edge recording
- 4-zone video masking for privacy protection
- Compact vandal-proof metal housing (IK10, IP67)
- 12V DC / PoE (802.3af), max 3 W power consumption

■ EASY Vision

Remote live view, playback, push alarm notifications, PTZ control, device sharing via QR code. Manage all Easy MT devices from a single app.

Available on iOS App Store & Google Play

TECHNICAL SPECIFICATIONS

Camera	
Image Sensor	1/2.8" 4MP CMOS
Max. Resolution	4MP
Min. Illumination	0.01 Lux @ F2.0, 0 Lux with illumination
IR Distance	30 m
Warm Light Distance	30 m
Day/Night	Auto (ICR) / Color / B/W
Gain Control	Auto / Manual
Audio	
Built-in Microphone	Yes
Network	
Network Port	RJ-45 (10/100 Base-T)
Protocol	TCP/IP; UDP; HTTP; DHCP; DDNS; FTP; UPnP
Interoperability	ONVIF, CGI, P2P, SDK, API
Storage	Micro SD card (max 256 GB)
Management Software	EASY Vision app (iOS / Android), ONVIF, CGI, compatible VMS
Mobile Phone	EASY Vision (iOS / Android)
Browser	IE8+
Structure	
Casing	Metal
Dimensions	Ø97 x 82 mm
Net Weight	0.42 kg (0.93 lb)

Lens	
Lens Type	Fixed
Focal Length	2.8 mm
Max. Aperture	F2.0
Video	
Video Compression	H.265; H.264
Main Stream	4MP (1~20/25 fps)
Sub Stream	D1 (1~25/30 fps)
Image Enhancement	BLC, Digital WDR, 3D NR, Mirror
White Balance	Auto / Manual
Video Masking	4 zones
Power	
Power Supply	12V DC (±30%) / PoE (802.3af)
Max. Power Consumption	3 W
Environment	
Operating Temperature	-20°C to +60°C (-4°F to +140°F)
Storage Temperature	-30°C to +60°C (-22°F to +140°F)
Operating Humidity	≤95% RH
Protection	IP67, IK10